



DAM-2550 A

Digital Selective Remote Microphone Unit

Made
in
Germany



EN 54 16

APPLICATION

- Public Address and Voice Alarm
- Background Music
- Audio Visual

AREA OF USE

- Health
- Education
- Retail
- Hospitality
- Stadiums
- Transportation
- Theme parks
- Military

OVERVIEW

The Digital-Selective-Remote-Microphone-Unit DAM-2550 A is a microcontroller-supported, fully digital microphone call station with bidirectional digital transmission of data and audio signals (VoIP), as well as power supply via Ethernet data cable (PoE). The functional assignment of all memory keys of the call station and the optional expansion modules is optional. There are 10 freely programmable memory keys, a ten-key pad for individual or group calls, two covered ones (Alarm) buttons, a large, easy-to-use talk button, and (+) and (-) function buttons (for changing the sound carrier volume, sensitivity of the sound carrier input, microphone volume and characteristics compressor and gate function) are available. Through the extension software license, the station can be monitored in accordance with EN54-16.

The graphic touch screen full colour LCD display with 320 x 240 pixels allows the plain text display and pictograms of all the necessary system information. It also allows viewing of the selected groups and rooms in numerical form and plain text and shows the currently occupied ones when they are called. The full colour display is used to visualize error states.

The DAM-2550 A is equipped with high-performance A/D and D/A converters with 128x oversampling for pristine reproduction of speech and music. The input and output channel gain is from 0 to 59.9 dB or 0 to 63.5 dB adjustable in 0.5 dB increments.

A compressor/gate function (single adjustable), as well as an automatic volume adjustment of the microphone input by means of an automatic gain control (AGC) to ensure maximum intelligibility of the announcements is a built-in feature.

It is also possible to connect an external sound carrier device to the built-in stereo cinch sockets in order to feed a music signal into the PADES@2000 system. Up to 8 digital remote microphone extension modules DAM-2551 A can be connected to a DAM-2550 A plant.

PADES [®] 2000-Series



TECHNICAL DATA

Microphone	Electret Cardioid
Gooseneck length	280 mm
Memory buttons	10, illuminated
Alarm buttons	2, illuminated, covered
Keyboard block	10+ 6
Talk button	1
Full colour LCD display	TFT dot matrix, 320 x 240 px, 88.9 mm (3.5")
Line input	100 – 500 mV
Frequency response	(-3dBu) at 200 – 15,000 Hz
THD	Less than 1% @ 1 KHz
Power supply	48 V DC (PoE)
Current consumption	125 mA (max.)
System connection	RJ-45, Ethernet
Operating temperature	-5 to + 50 C°
Dimensions (W x H x D)	250 x 45 x 196 mm
Weight	1.55 kg



Member of the ZVEI - Central Association
for the Electrical Engineering and Electrical
Industry eV Safety Association



All rights reserved.

Information contained in this document is believed to be accurate, however no representation or warranty is given and Audemo-systems in Germany assumes no liability with respect to the accuracy of such information.

PADES [®] 2000-Series

AUDEMO - SYSTEMS GmbH (Headquarter)

Schatzbogen 62 81829 Munchen
Tel.: +49 (0) 89 1 4 56 78 47 - 0, Fax: +49 (0) 89 1 4 56 78 47- 2900
info@audemo-systems.de, www.audemo-systems.de

AUDEMO Middle East General Trading (Middle East & North Africa)

P.O.BOX: 43594, Abu Dhabi, United Arab Emirates
Tel : +971 (02)6263836, info@audemo-me.com