



## DCM-2860A

### GPS Radio Receiver Module

Made  
in  
Germany



#### APPLICATION

- Public Address and Voice Alarm
- Background Music
- Audio Visual

#### AREA OF USE

- Health
- Education
- Retail
- Hospitality
- Stadiums
- Transportation
- Theme parks
- Military

#### TECHNICAL DATA

Power supply	24 VDC via the 3 pin
Cable connection	3 pole, shielded cable with a cross-section of 0.33-2.5mm <sup>2</sup>
Connection length	200 m
Temperature range	- 30 to +55 °C
Protection class	IP54
Dimensions (W x H x D)	75 x 41 x 89.5 mm
Weight	84g
Current consumption	80mA maximum
Output signal	DCF time telegram ( without weather data)

#### All rights reserved.

Information contained in this document is believed to be accurate, however no representation or warranty is given and Audemo-systems in Germany assumes no liability with respect to the accuracy of such information.

**ZVEI:**

Member of the ZVEI - Central Association  
for the Electrical Engineering and Electrical  
Industry eV Safety Association



**PADES** <sup>®</sup> 2000-Series

#### AUDEMO - SYSTEMS GmbH (Headquarter)

Schatzbogen 62 81829 Munchen  
Tel.: +49 (0) 89 1 4 56 78 47 - 0, Fax: +49 (0) 89 1 4 56 78 47- 2900  
info@audemo-systems.de, www.audemo-systems.de

#### AUDEMO Middle East General Trading (Middle East & North Africa)

P.O.BOX: 43594, Abu Dhabi, United Arab Emirates  
Tel : +971 (02)6263836, info@audemo-me.com